



CW-0403

# Super Quick Sanding Sealer

## Product Data Sheet

### PRODUCT DESCRIPTION

Super Quick Sanding Sealer is a quick drying, lower odor sealer for use on bare interior wood surfaces. It provides complete sealing of the wood and is easy to sand.

### TYPICAL USES

Formulated for use on bare interior wood surface in both residential and commercial buildings. Super Quick is ideal for use on doors, trim, cabinets and paneling.

### FINISHES AVAILABLE

CW-0403 Light Amber Color

### PHYSICAL PROPERTIES(CW-0403)

Resin Type	Oil Copolymer with Zinc Stearate
Clean-up Solvent	Mineral Spirits
Solids by Weight	36 %
Solids by Volume	27 %

Recommended Dry Film Thickness per Coat 1 – 1.5 mils

Wet Film to Achieve DFT 4 – 5.5 mils

Theoretical Coverage @ 1 mil 433 ft<sup>2</sup>/gallon

Practical Coverage at Recommended DFT<sup>1</sup> 292 – 438 ft<sup>2</sup>/gallon

Dry Times<sup>2</sup>  
@ 70° F (21° C) and 50% R.H.  
Set to Touch 30 minutes  
Sand 2 hours  
Recoat after sanding

VOC's 550 grams/liter

1 Spread rates are estimates based on products volume solids and make no allowance for material loss during application. Actual spread rates may vary dependent on applicator experience, surface porosity and texture.

2 Dry times may vary depending upon temperature, humidity and degree of air movement.

### SPECIFICATIONS

#### Interior Wood

1 ct CW-0403 Super Quick Sanding Sealer  
2 cts CW-Series Quick Dry Varnish  
Or

1 ct CW-0403 Super Quick Sanding Sealer  
2 cts CW-Series Super Varnish

May also be used as a self-sealing 2 coat finish system.

#### DO NOT USE AS A SEALER FOR POLYURETHANE FINISHES.

This product meets or exceeds Master Painters Institute (MPI) # 102 approval standard.

For more detailed recommendations, please contact your local Diamond Vogel Sales Representative.

## **SURFACE PREPARATION**

The wood surfaces must be clean, dry and free from dirt, dust, wax and grease. **Bare surfaces must be properly prepared and primed prior to application of this product.**

### **Bare Wood Surfaces**

- Eliminate imperfections by sanding the wood thoroughly; begin with a medium grit sandpaper progressing to a fine grit. Always sand in the direction of the wood grain. Remove dust particles with a tack rag.
- For a smooth topcoat on open grain woods, use Old Masters Woodgrain Filler and apply according to label instructions.
- If wood will be stained, apply prior to using this product. Allow the stain to dry thoroughly.

### **Previously Finished Wood**

- Sand with a fine grit sandpaper to remove surface imperfections and gloss. Remove sanding dust with a tack rag.
- Wax and/or polish are best removed by wiping thoroughly with mineral spirits. Change rags often and wash until all wax and/or polish is removed.

## **APPLICATION**

- Stir material before and during use. For projects requiring more than one container, intermix to ensure gloss uniformity.
- Equipment must be clean prior to start. Flush airless lines with clean mineral spirits.
- Apply by brush, pad, roller airless spray, HVLP or conventional spray. A good quality natural bristle brush will make application easier. Use of a ¼" nap mohair or foam roller, lambskin pad type applicator or airless tip size of .011 to .013 is recommended.
- Apply the product in full, even coats and maintain a wet edge. Apply enough material to fully saturate the surface. On extremely porous wood, two coats may be required to completely seal the surface. Allow to dry and sand lightly and remove all dust with a tack rag prior to topcoating.
- Do not thin.

## **ENVIRONMENTAL VARIABLES**

Apply when air and surface temperatures are above 40° F (4° C). While this product is not subject to freezing, curing is affected by temperature, humidity and air movement; cold temperatures will increase drying time. Application at elevated temperatures, wind conditions, and/or low humidity may require special application procedures to achieve proper film formation. Do not apply to surfaces that are damp.

## **CLEAN-UP**

Clean up all equipment using mineral spirits.

## **CAUTIONS**

For Interior use only  
Not intended for use on floors  
Do not apply below 40° F.  
Protect from freezing  
Do not take internally  
Use with adequate ventilation  
**KEEP OUT OF REACH OF CHILDREN**

\*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel Paints does not control the application of its products, or the condition of the surfaces to which they are applied, Diamond Vogel Paint's liability will under no circumstances exceed replacement of the product.