

# Grain Stain<sup>®</sup>

**Grain Stain Semi-Transparent Oil Stain is a high quality deep penetrating oil stain designed to protect and enrich the natural beauty of wood, allowing the natural wood texture to show through.**

## Features:

- Mildew Resistant
- Available in Natural and White Tint Bases
- Available in Ready mixed colors
- UV Resistance
- Water Repellant



For more information call:

DV Representative  
( ) -

Diamond Vogel  
1-800-72VOGEL  
[www.diamondvogel.com](http://www.diamondvogel.com)

Formulated for use on residential and commercial exterior new or bare exterior rough and smooth wood surfaces. Ideal for use on decks, patios, outdoor furniture, exterior siding, fences, shakes and trim.

Grain Stain Semi-Transparent Oil Stain

# Surface Preparation

# Physical Properties

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared prior to application of this product.**

### Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry.

Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

### Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

### **PHYSICAL PROPERTIES(AG-0320)**

Resin Type	Linseed Oil
Clean-up Solvent	Mineral Spirits
Finish	Not Applicable
Solids by Weight	34 %
Solids by Volume	30 %
Recommended Dry Film Thickness per Coat	Not Applicable
Theoretical Coverage @ 1 mil	474 ft <sup>2</sup> /gallon
Practical Coverage at Recommended DFT	150 – 300 ft <sup>2</sup> /gallon
<u>Dry Times</u> @ 70° F (21° C) and 50% R.H.	24 – 36 hours Recoat 2 to 4 hours
VOC's (Range from 544 – 550 depending on color and base)	

# System Recommendation

### Substrate

Exterior Wood

### Primer

AG-Series Grain Stain Semi-Transparent Oil Stain

### Finish

May be used as a one (1) or two (2) coat system. Two (2) coats are recommended (applied wet on wet) for optimum performance and color uniformity.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



[www.diamondvogel.com](http://www.diamondvogel.com)  
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.