

Grain Stain[®]

Grain Stain Deck Stain is a premium quality, penetrating exterior transparent oil stain. It is designed to provide superior color retention and outstanding clarity while protecting and enhancing the natural beauty of the wood.

Features:

- Trans-Oxide Pigments
- Available in:
Natural Tone Redwood,
Natural Tone Cedar,
Colorado Cedar
- Water Repellant
- Mildew Resistance



For more information call:

DV Representative
() -

Diamond Vogel
1-800-72VOGEL
www.diamondvogel.com

Grain Stain Deck stain penetrates deep into the wood, allowing the natural wood texture to show through, while the tough scuff-resistant finish resists wear from foot traffic. Formulated for use on new or bare, rough and smooth, exterior wood surfaces. Ideal for use on decks, fencing, wood patios, outdoor furniture, siding, shakes and trim.

Grain Stain Transparent Oil Deck Stain

Surface Preparation

Physical Properties

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared prior to application of this product.**

Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry.

Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

PHYSICAL PROPERTIES(AG-8343)

Resin Type	Modified Alkyd
Clean-up Solvent	Mineral Spirits
Finish	Not Applicable
Solids by Weight	35 %
Solids by Volume	29 %
Recommended Dry Film Thickness per Coat	Not Applicable
Theoretical Coverage @ 1 mil	561 ft ² /gallon
Practical Coverage at Recommended DFT ¹	150 – 300 ft ² /gallon
Dry Times ² @ 70° F (21° C) and 50% R.H.	24 – 36 hours
VOC's	550 grams/liter

System Recommendation

Substrate

Exterior Wood

Primer

Self Priming

Finish

Grain Stain Transparent Oil Deck Stain

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



www.diamondvogel.com
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.