

Super Varnish

Super Varnish is a high quality interior alkyd resin varnish that exhibits outstanding durability. Super Varnish is formulated for easy application, resulting in a finish that will remain beautiful for years.

Features:

- Low Odor
- Outstanding Durability
- Gloss, Semi-Gloss and Satin finishes
- Apply by brush, pad, roller or spray application.



For more information call:

DV Representative
() -

Diamond Vogel
1-800-72VOGEL
www.diamondvogel.com

Formulated for use on new and previously finished interior wood surfaces in both residential and commercial buildings. Super Varnish is ideal for use on doors, trim and cabinets.

Super Varnish

Surface Preparation

Physical Properties

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared prior to application of this product.**

Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry.

Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

PHYSICAL PROPERTIES(CW-0303)

Resin Type	Alkyd
Clean-up Solvent	Mineral Spirits
Solids by Weight	51 %
Solids by Volume	44 %
Recommended Dry Film Thickness per Coat	1.5 – 2 mils
Wet Film to Achieve DFT	4 – 5.5 mils
Theoretical Coverage @ 1 mil	706 ft ² /gallon
Practical Coverage at Recommended DFT ¹	353 – 471 ft ² /gallon
<u>Dry Times</u> ² @ 70° F (21° C) and 50% R.H.	Touch 6 to 8 hours Recoat 12 hours
VOC's (ranges from 438 to 481 depending on finish)	438 grams/liter

System Recommendation

Substrate

Interior Wood

Primer

Self Sealing
CW-0403 Super Quick Sanding Sealer

Finish

CW-Series Super Varnish

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



www.diamondvogel.com
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.