

# SUPER QUICK

## Stearated Sanding Sealer

Super Quick Sanding Sealer is a quick drying, low odor sealer for use on bare interior wood surfaces. It provides complete sealing of the wood and is easy to sand.

### Features:

- Quick Drying
- Easy to sand
- Apply by brush, pad, roller or spray application.



For more information call:

DV Representative  
( ) -

Diamond Vogel  
1-800-72VOGEL  
[www.diamondvogel.com](http://www.diamondvogel.com)

Formulated for use on bare interior wood surface in both residential and commercial buildings. Super Quick is ideal for use on doors, trim, cabinets and paneling.

Super Quick Sanding Sealer

# Surface Preparation

# Physical Properties

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared prior to application of this product.**

### Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry.

Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

### Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

### **PHYSICAL PROPERTIES(CW-0403)**

Resin Type	Oil Copolymer with Zinc Stearate
Clean-up Solvent	Mineral Spirits
Solids by Weight	36 %
Solids by Volume	27 %
Recommended Dry Film Thickness per Coat	1 – 1.5 mils
Wet Film to Achieve DFT	4 – 5.5 mils
Theoretical Coverage @ 1 mil	433 ft <sup>2</sup> /gallon
Practical Coverage at Recommended DFT	292 – 438 ft <sup>2</sup> /gallon
<u>Dry Times</u> @ 70° F (21° C) and 50% R.H.	Set to Touch 30 minutes Sand 2 hours Recoat after sanding
VOC's	550 grams/liter

# System Recommendation

### Substrate

Interior Wood

### Primer

CW-0403 Super Quick Sanding Sealer

### Finish

CW-Series Quick Dry Varnish  
CW-Series Super Varnish

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



[www.diamondvogel.com](http://www.diamondvogel.com)  
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.