

DiaPRO[®]

Dia-Pro Ceiling and Wall Paint is a good quality interior latex flat finish. It has a matte flat appearance that provides a smooth, uniform look. With its spatter resistant formula, ease of application is greatly enhanced compared to standard formulations when roller applied.

Features:

- Low spatter formulation
- Available in:
Tintable White
- Flat Finish
- Apply by brush, roller or spray application.



For more information call:

DV Representative
() -

Diamond Vogel
1-800-72VOGEL
www.diamondvogel.com

Dia-Pro is formulated for use as a finish coat on residential or commercial interior ceilings and walls constructed of plaster, wall board, wood or masonry.

**Dia-Pro Ceiling and Wall
Paint Interior Latex Flat**

Surface Preparation

Physical Properties

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared and primed prior to application of this product.**

Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry. Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

Physical Properties (DF-1525)

Resin Type	P.V.A. Emulsion
Clean-up Solvent	Water
Finish	5-10 @ 85°
Solids by Weight	47 %
Solids by Volume	31 %
Recommended Dry Film Thickness per Coat	1.5 – 2 mils
Wet Film to Achieve DFT	5 – 6.5 mils
Theoretical Coverage @ 1 mil	497 ft ² /gallon
Practical Coverage at Recommended DFT	249 – 331 ft ² /gallon
<u>Dry Times</u> @ 70° F (21° C) and 50% R.H.	Touch 1 to 2 hours Recoat 4 hours
VOC's	99 grams/liter

System Recommendation

<u>Substrate</u>	<u>Primer</u>	<u>Finish</u>
Interior Wood	DU-1508 Latex Enamel Undercoat CU-1401 Alkyd Enamel Undercoat	Dia-Pro Ceiling & Wall Paint
Drywall	DU-Series Interior Latex Primers	Dia-Pro Ceiling & Wall Paint
Plaster	CU-1401 Alkyd Enamel Undercoat DU-1502 Interior Primer/Sealer	Dia-Pro Ceiling & Wall Paint
Smooth Block	DU-1502 100% Acrylic Primer/Sealer	Dia-Pro Ceiling & Wall Paint
Porous Block	BF-Series Block Fillers	Dia-Pro Ceiling & Wall Paint
Ferrous Metal	AZ-Series Cote-All Primers V-Cote 200 Acrylic Maintenance Primer (MC-Series)	Dia-Pro Ceiling & Wall Paint
Galvanized & Aluminum	V-Cote 200 Acrylic Maintenance Primer (MC-Series)	Dia-Pro Ceiling & Wall Paint

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



www.diamondvogel.com
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.