

## **PRO** *plus*

**Pro Plus is our best commercial interior latex with a durable finish. Pro Plus gives the flexibility of being used as a high build finish with easy application characteristics.**

### **Features:**

- High Build Characteristics
- Available in: Tintable White and Dark Bases
- Flat, Eggshell, Semi-Gloss & Gloss Finishes
- Apply by brush, roller or spray application.



For more information call:

DV Representative  
( ) -

Diamond Vogel  
1-800-72VOGEL  
[www.diamondvogel.com](http://www.diamondvogel.com)

May be used on residential and commercial interior walls, ceilings, trim and doors. Designed as a finish coat for interior drywall, wood, plaster and masonry surfaces.

**Pro Plus Interior Latex Finishes**

# Surface Preparation

# Physical Properties

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared and primed prior to application of this product.**

### Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry. Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

### Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

### PHYSICAL PROPERTIES(DF-1625)

Resin Type	P.V.A. Emulsion
Clean-up Solvent	Water
Gloss	0-5 @ 85°
Solids by Weight	52 %
Solids by Volume	32 %
Recommended Dry Film Thickness per Coat	2 - 3 mils
Wet Film to Achieve DFT	6 - 9 mils
Theoretical Coverage @ 1 mil	513 ft <sup>2</sup> /gallon
Practical Coverage at Recommended DFT	171 - 256 ft <sup>2</sup> /gallon
<u>Dry Times</u> @ 70° F (21° C) and 50% R.H.	Touch 1 hour Recoat 4 hours

	Flat	Eggshell	Semi-Gloss	Gloss
VOC's	186-214 g/L	85-90 g/L	62-66 g/L	62-66 g/L
	(Range from 62 – 214 depending on base)			

# System Recommendation

<u>Substrate</u>	<u>Primer</u>	<u>Finish</u>
Interior Wood	DU-1508 Latex Enamel Undercoat CU-1401 Alkyd Enamel Undercoat	DF/DE/DS/DH Series Pro Plus Interior
Drywall	DU-Series Interior Latex Primers Self Priming	DF/DE/DS/DH Series Pro Plus Interior
Plaster	CU-1401 Alkyd Enamel Undercoat DU-1502 Interior Primer/Sealer	DF/DE/DS/DH Series Pro Plus Interior
Interior Block (Porous)	BF-Series Block Fillers	DF/DE/DS/DH Series Pro Plus Interior
Ferrous Metal	AZ-Series Cote-All Primers V-Cote 200 Acrylic Maintenance Primer (MC-Series)	DF/DE/DS/DH Series Pro Plus Interior
Interior Block (Smooth)	DU-1502 100% Acrylic Primer/Sealer	DF/DE/DS/DH Series Pro Plus Interior
Galvanized & Aluminum	V-Cote 200 Acrylic Maintenance Primer (MC-Series)	DF/DE/DS/DH Series Pro Plus Interior

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



www.diamondvogel.com  
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.