

# SUPER QUICK 30

Super Quick 30 is a quality 100% acrylic latex satin spray enamel specifically designed for interior or exterior wood trim and primed metal. It is a tough, durable, washable enamel that is non-yellowing with good gloss and color retention.

## Features:

- Durable Enamel Finish
- Excellent early Block Resistance
- Available in Satin Finish
- Non-Yellowing
- Tintable to All White Base Formulas.



For more information call:

DV Representative  
( ) -

Diamond Vogel  
1-800-72VOGEL  
[www.diamondvogel.com](http://www.diamondvogel.com)

Super Quick 30 is formulated for use on residential and commercial interior or exterior wood trim, cabinets and metal doors.

Super Quick 30

# Surface Preparation

All surfaces must be cured, clean sound, dry and free of all dirt, dust, efflorescence, wax, oil grease, chalk and any other contamination that would interfere with the new coating adhesion. **Bare surfaces must be properly prepared and primed prior to application of this product.**

## Previously Painted Surfaces

Power or hand washing is recommended to remove contamination. If oil or grease is present, the use of a cleaner/degreaser is required. All cleaning residue must be completely rinsed from the surface. Allow to dry. Remove all loose coatings and corrosion by scraping, sanding or other abrading method. Dull glossy, slick and/or non-porous surfaces with sandpaper. Patch and fill areas as needed. Spot prime bare areas with appropriate primer.

## Mildew

Remove by using a solution of one (1) part household bleach and three (3) parts water. Apply to mildewed area and scrub. Allow solution to remain on the surface for 3 to 5 minutes then rinse completely and allow to dry before coating application.

# Physical Properties

## PHYSICAL PROPERTIES(DS-1561)

Resin Type	Acrylic Latex
Clean-up Solvent	Water
Finish	30-35 @ 60°
Solids by Weight	45 %
Solids by Volume	32 %

Recommended Dry Film Thickness per Coat	1 – 1.5 mils
Wet Film to Achieve DFT	3 – 5 mils

Theoretical Coverage @ 1 mil	513 ft <sup>2</sup> /gallon
------------------------------	-----------------------------

Practical Coverage at Recommended DFT	342 – 513 ft <sup>2</sup> /gallon
---------------------------------------	-----------------------------------

<u>Dry Times</u> @ 70° F (21° C) and 50% R.H.	Touch ½ to 1 hour Recoat 2 – 3 hours Dry before use 24 hrs
---	--

VOC's

# System Recommendation

<u>Substrate</u>	<u>Primer</u>	<u>Finish</u>
Interior Wood	DU-1508 Latex Enamel Undercoat CU-1401 Alkyd Enamel Undercoat	DS-Series Super Quick 30
Ferrous Metal	AZ-Series Cote-All Primers V-Cote 200 Acrylic Maintenance Primer (MC-Series)	DS-Series Super Quick 30
Exterior Wood	BU-Series Acrylic Primers AU-Series Alkyd Primers	DS-Series Super Quick 30
Galvanized & Aluminum	V-Cote 200 Acrylic Maintenance Primer (MC-Series)	DS-Series Super Quick 30

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



[www.diamondvogel.com](http://www.diamondvogel.com)  
1-800-72VOGEL (728-6435)

The contents of this literature are for informational purposes only. Consult the product data sheet for complete information.